



Features

- ▶ Hi fidelity
- ▶ Wi-fi router
- ▶ Easy to use
- ▶ Good GUI
- ▶ 31bands GEQ for in/out
- ▶ Android App

Specification

Model	DS428E	DS226E	DS224E
Input/Output	4 in 8 out	2 in 6 out	2 in 4 out
Input/Output Gain	-40~+12dB, step 0.1dB		
Max. Output level	20dBu		
Input/Output Delay	0ms~2s, step 21us		
Input/Output PEQ	Each channel has 9-band parametric equalizer		
EQ Gain	-30~+15dB, step 0.1dB		
EQ Type	PEQ, Low shelf, High Shelf, Phase Shelf (optional)		
EQ Frequency	19.7~21.9 KHz		
EQ Bandwidth	PEQ 0.017~21.9KHz		
Input GEQ	Each channel has 31-band graphic equalizer (1/3 oct)		
Crossover	Frequency: 19.7~21.9KHz		
	Slop: FLAT THRU, 12dB, 24dB, 36dB, 48dB		
	Butterworth 6dB, 12dB, 18dB, 24dB, 48dB		
	Bessel 12dB, 18dB, 24dB, 48dB Linkwitz-Riley 24dB, 48dB		
Compressor Threshold	Gate: -20~+20dBu, step 0.5dBu		
	Ratio: 1.2, 1.5, 2, 3, 4, 6, 10, 20, 40, 128:1		
Attack time	1~100ms, step 1ms		
Release time	50~1000ms, step 50ms		
Dynamic range	112 dB		
CMRR	55dB		
Separation	95dB		
Distortion Degree	0.002% (1KHz, 1Vms)		
Voltage	90-240V/AC 50Hz-60Hz		
Weight	3.8 kg		
Size	482mm×213mm×88mm		