



Features

- Designed for cinema system, intelligent home, home theater etc. to match with 5.1 or 7.1 multi channels.
- 1U Rack design with small dimension and big output power
- Modular design, each channel is fully separately and without any interference to other channels.
- High efficiency SMPS and big current storage, intelligent Limiter, multi-protection functions

Specification

2 Technical Specification

Model	DSQ2400	DSQ7200	DSQ10000
Channel	4	4	4
Output Power (All channels driven output power, THD=1%)			
8Ω	350Wx4	800Wx4	1300Wx4
4Ω	500Wx4	1500Wx4	2400Wx4
2Ω	600Wx4	1800Wx4	2600Wx4
Frequency Response (@8Ω)	20Hz-20KHz, ±0.3dB		
Slew Rate	50V / us		
THD+N	< 0.3%		
IMD-SMPTE	< 0.3%		
SNR	> 105dB		
Crosstalk	> 75dB		
Damping Factor	> 800 (8Ω, 20Hz-200Hz)		
Input Impedance	20K (bal), 10K (unbal)		
Power Efficiency	> 85%		
Height	1U		
Product Dimension(mm)	483x375x44	483x430x44	483x430x44
Packing Dimension(mm)	530x530x90mm (WxDxH)		
Net Weight	7.5Kg	9.5Kg	10.5Kg
Gross Weight	9.2Kg	11.2Kg	12.2Kg

Manufacture ASL Co. We guarantee 5 years for all ASL products fully

Homepage www.aslaudio.co.kr Email: asl@aslaudio.co.kr / hgkim@aslaudio.co.kr

Address 753-1 Gyongchun-ro, Gapyong-gun Gyeonggi-do, Korea Post code: 12451

Specifications subject to change without prior notice. All rights reserved 2017 ASL Code: N A Rev.: 16 - 0 6 / 0 6