

Features



Applications:

- Meeting room Medium
- large conference rooms
- Courtrooms
- Auditoriums
- Multi-purpose spaces
- Stadium
- Professional performance

Key Features :

- ▲ Sampling rate 96k24BIT
- ▲ 7 PEQS per input and 7PEQS per output.
- ▲ High and low pass filter,ALLpass
- ▲ Support for multiple connection mode , USB , TCP/IP , RS232 , RS485
- ▲ Support mobile APP wireless control
- ▲ Support multiple machines networking and joint debugging, remote monitoring

Signal Processor	ADI SHARC 21489
Audio latency	2.8ms
AD DA converters	24 bit
Sampling rate	96Khz
Input Impedance	22KΩ
Output Impedance	150Ω
Frequency Response	20Hz-40Khz(+/-0.5dB)
THD+N	-90dB(0dBu@ 1Khz A-weight Line
SNB	108dB(16dBu@ 1Khz A-weight Line
Communication port	USB, RS232, TCPIP
LED Status indicators	Clip, Level, EDIT, Mute
PEQ	7 for in and out
Filter	High and Low, Allpass
Mobile APP	Support
Multiple connection	Support
Dante	Option
Delay	1 second
Control software	Windows 7/8/10
Operation temperature	-20°C~80°C
Main Voltage	AC 90-264V 50/60Hz
Dimensions	483mm x 45mm x 226mm(WHD)
Net Weight	3.2Kg