

## Features



- ▶ Hi fidelity
- ▶ Fine component
- ▶ Easy to rigging
- ▶ Heavy duty grill
- ▶ Durable finish
- ▶ 5 years warranty

## Specification

Input channels	4
Rated input power	220V 60Hz
Output power	600watts x 4 @8Ω
	900watts x 4 @4Ω
Input sensitivity	0dB(0.775Vrms)/1V/1.4V
Frequency response	20Hz-20Khz(+/-0.38dB)
Impedance	Balance:30KΩ Unbalance:15KΩ
Slew rate	30Vus >
Damping factor	300>
Crosstalk	70dB@1Khz >
S/N rate	100dB>
Total harmonic distortion	0.1 1Khz 8Ω @1W<
Inter modulation distortion	0.2% 8Ω @1W<
Dimensions	484mm x 100 x 405(WHD)
Weight	21Kg

Manufacturer ASL Co. We guarantee 5 years for all ASL products fully

Homepage [www.aslaudio.co.kr](http://www.aslaudio.co.kr) Email:[asl@aslaudio.co.kr](mailto:asl@aslaudio.co.kr) / [hgkim@aslaudio.co.kr](mailto:hgkim@aslaudio.co.kr)

Address 900, Seongjugayasan-ro, Suryun-myeon, Seongju-gun, Gyeongsangbuk-do, Republic of Korea Post code:40064

Specifications subject to change without prior notice. All rights reserved 2018 ASL Code: N A Rev.: 19 - 0 9 / 01