

Enjoy the sound at your party



EXP-05

EXP-08

EXP-10

EXP-12

EXP-15

EXP-12M

	EXP-05	EXP-08	EXP-10
System	Two way passive	Two way passive	Two way passive
Components	Hi:1" silk dome, Low:5.5"	Hi:1" driver, Low:8"	Hi:1" driver, Low:10"
Voice coil	Hi:25mm, Low:30mm	Hi:34mm, Low:50mm	Hi:34mm, Low:50mm
Frequency range	120Hz-19Khz	100Hz-19Khz	90Hz-19Khz
Magnetic material	Hi-Ferrite Low-Ferrite	Hi-Ferrite Low-Ferrite	Hi-Ferrite Low-Ferrite
Impedance	Hi:8Ω, Low:8Ω	Hi:8Ω, Low:8Ω	Hi:8Ω, Low:8Ω
Coverage	90°x90°(HxV)	90°x60°(HxV)	90°x60°(HxV)
Sensitivity	86 dB @1m/1watt	98 dB @1m/1watt	98 dB @1m/1watt
Maximum SPL	106dB SPL	120dB SPL	123dB SPL
Power handling	60watts@AES	150watts@AES	200watts@AES
Enclosure shape	Trapezoidal	Trapezoidal	Trapezoidal
Enclosure material	Plywood	Plywood	Plywood
Rigging Point	1 bolt	1 bolt	1 bolt
Paint	Polyurethane	Polyurethane	Polyurethane
Finish	Texture	Texture	Texture
Dimensions(WHD)	185mmx290mmx130mm	283mmx430mmx290mm	337mmx513mmx330mm
Weight	3.56Kg	8.5Kg	11.3Kg

	EXP-12	EXP-12M	EXP-15
System	Two way passive	Two way passive	Two way passive
Components	Hi:1" driver, Low:12"	Hi:1" driver, Low:12"	Hi:1" driver, Low:15"
Voice coil	Hi:44mm, Low:60mm	Hi:44mm, Low:60mm	Hi:44mm, Low:60mm
Frequency range	80Hz-19Khz	80Hz-19Khz	70Hz-19Khz
Magnetic material	Hi-Ferrite Low-Ferrite	Hi-Ferrite Low-Ferrite	Hi-Ferrite Low-Ferrite
Impedance	Hi:8Ω, Low:8Ω	Hi:8Ω, Low:8Ω	Hi:8Ω, Low:8Ω
Coverage	90°x60°(HxV)	90°x60°(HxV)	Horizon90°x60°(HxV)
Sensitivity	99 dB @1m/1watt	99 dB @1m/1watt	99 dB @1m/1watt
Maximum SPL	124dB SPL	124dB SPL	125dB SPL
Power handling	250watts@AES	250watts@AES	300watts@AES
Enclosure shape	Trapezoidal	Trapezoidal	Trapezoidal
Enclosure material	Plywood	Plywood	Plywood
Rigging Point	1 bolt	1 bolt	1 bolt
Paint	Polyurethane	Polyurethane	Polyurethane
Finish	Texture	Texture	Texture
Dimensions(WHD)	360mmx571mmx360mm	331mmx571mmx440mm	422mmx696mmx465mm
Weight	15Kg	15Kg	21.5Kg