



## Features

- Designed for cinema system, intelligent home, home theater etc. to match with 5.1 or 7.1 multi channels.
- 1U Rack design with small dimension and big output power
- Modular design, each channel is fully separately and without any interference to other channels.
- High efficiency SMPS and big current storage, intelligent Limiter, multi-protection functions

## Specification

Model	DS6600	DS8600
Channel	6	8
Output Power ( All channels driven output power, THD=1% )		
8Ω	350*6	350*8
4Ω	500*6	500*8
2Ω	600*6	600*8
Frequency Response ( @8Ω )	20Hz ~ 20KHz, ±0.3dB	
Slew Rate	50V/us	
THD+N	< 0.3%	
IMD-SMPTE	< 0.3%	
SNR	> 105dB	
Crosstalk	> 75dB	
Damping Factor	> 800(8Ω, 20Hz ~ 20KHz)	
Input Power/Voltage	1V	
Input Impedance	20K ( bal ) , 10K ( unbal )	
Power Requirements	AC 220V ~ 240V(50 ~ 60Hz)	
Height	1U	
Product Dimension(mm)	483*430*44mm	
Packing Dimension(mm)	530*530*90mm	
Net Weight	9.3KG	10.9KG
Gross Weight	10.9KG	12.5KG